



Innovative Chemical Solutions for the Public Safety Industry

Shield Solutions, LLC

W1737 Washington Rd. Oconomowoc, WI 53066 USA

Aluminum Cleaner/Brightener Directions

Pump Up Foam Sprayer Application Method

- 1.) Read all warnings prior to application. Test product on a small inconspicuous area first.
- 2.) Goggles must be worn while working with Shield Solutions™ Aluminum & Metal Cleaner / Brightener. For sensitive skin, use rubber gloves when handling the product.
- 3.) Pour approximately 36oz (1.1L) of Aluminum & Metal Cleaner/ Brightener into the 48oz (1.4L) Pump-Up Foam Sprayer. Pump until a sufficient pressure is achieved. (About 15-20 times)
- 4.) **Thoroughly wet the surface under the area to be cleaned. After use of product thoroughly rinse the floor. DISCOLORATION OF FLOORING MAY OCCUR IF THIS STEP IS NOT FOLLOWED.**
- 5.) Test the foam sprayer to determine proper foam consistency. Adjustments to the foam consistency can be made by turning the white foam tip, counter clockwise for wet foam, clockwise for dry.
- 6.) Spray a generous amount of foam onto the desired surface to be cleaned. **NOTE: The surface to be cleaned should be dry prior to application.** Only foam an area that can be worked in 10 minutes or less from start to finish. Do not allow product to stand on the surface for an extended period of time (discoloration may occur). Product can be foamed onto brush and applied to surface; this will reduce surface contact time.
- 7.) Agitate the foam with a Soft Bristle Brush. A circular motion works best where applicable.
- 8.) Thoroughly flush treated area with cold water to completely remove any remaining product. **NOTE: It is recommended that the vehicle be washed with Shield Solutions™ Vehicle Wash upon completion of aluminum & metal trim cleaning, to assure all remaining Aluminum & Metal Cleaner / Brightener is removed.**
- 9.) Repeat this process if necessary, to achieve the desired effect.
- 10.) Pour the unused portion of Aluminum & Metal Cleaner / Brightener back into the original container for storage and rinse the Pump-Up Foam Sprayer thoroughly when finished.
- 11.) When cleaning has been completed, we recommend applying Shield Solutions™ Detailer to all surfaces for the ultimate shine and protection.

Cautions and Warnings

- Do not ingest, may be harmful or fatal if swallowed
- Avoid eye contact
- Vapor mist may cause irritation
- Product may cause slight irritation to skin
- Product may cause discoloration to some chromed plastic parts, especially if left in contact for an extended period of time
- Prolonged exposure to certain surfaces may cause discoloration
- Exposure to untreated concrete may cause discoloration
- Use in well ventilated areas
- Use safety goggles or safety glasses with side shields to avoid splash exposure to the eyes
- For sensitive skin, use rubber gloves when handling product
- Avoid surface contact for an extended period of time
- Thoroughly wet the surface under the area to be cleaned
- Rinse treated areas thoroughly with water, including outer lip on side and tail boards
- Keep product out of direct sunlight
- Store in a cool dry area, do not store near flames or other heat sources
- Keep containers tightly closed
- Make sure all containers are properly labeled
- Wash hands thoroughly after handling
- Read and understand the MSDS before using any chemical product
- Shield Solutions is not responsible for damage caused by misuse of this product.

W1737 Washington Dr. Oconomowoc, WI 53066 USA | 920-474-7502 ~ 877-474-7501 | www.shieldsolutionsllc.com